

WHAT IS CLAIMED IS:

1. A textile-reactive preparation comprising:
a durable-press resin capable of forming a covalent bond with a textile and
capable of imparting wrinkle-resistance to said textile, and
5 a resin-reactive modifier capable of imparting a soft hand and tear/abrasion
resistance to said textile, said resin-reactive modifier comprising reactive
groups capable of forming a covalent bond with said durable-press resin.

10 2. A textile-reactive preparation according to Claim 1 wherein said resin-reactive
modifier comprises reactive building blocks and rubbery building blocks.

15 3. A textile-reactive preparation according to Claim 2 wherein said resin-reactive
modifier comprises at least one hydroxyl reactive group per molecule.

20 4. A textile-reactive preparation according to Claim 2 wherein said resin-reactive
modifier is selected from the group consisting of butadiene polymer and hydrogenated
butadiene polymer comprising at least one hydroxyl reactive group per molecule.

25 5. A textile-reactive preparation according to Claim 2 wherein said durable-press
resin is DMDHEU.

30 6. A method for treating a textile comprising:
exposing a textile to an aqueous solution or suspension of a textile-reactive
preparation comprising i) a durable-press resin capable of forming a
covalent bond with said textile and capable of imparting wrinkle-resistance
to said textile, ii) a resin-reactive modifier capable of imparting a soft hand
and tear/abrasion resistance to said textile, said resin-reactive modifier
comprising reactive groups capable of forming a covalent bond with said
durable-press resin, and optionally, iii) a catalyst;
removing said treated textile from the aqueous solution;

5

10

15

20

25

30

drying said treated textile; and
curing said treated textile;
to give a treated textile that exhibits durable wrinkle resistance, soft hand, and
tear/abrasion resistance.

7. A method according to Claim 6 wherein said resin-reactive modifier comprises
reactive building blocks and rubbery building blocks.

8. A method according to Claim 7 wherein said resin-reactive modifier comprises at
least one hydroxyl reactive group per molecule.

9. A method according to Claim 7 wherein said resin-reactive modifier is selected
from the group consisting of butadiene polymer and hydrogenated butadiene polymer
comprising at least one hydroxyl reactive group per molecule.

10. A method according to Claim 7 wherein said durable-press resin is DMDHEU.

11. A treated textile prepared by the method comprising:
exposing a textile to an aqueous solution or suspension of a textile-reactive
preparation comprising i) a durable-press resin capable of forming a
covalent bond with said textile and capable of imparting wrinkle-resistance
to said textile, ii) a resin-reactive modifier capable of imparting a soft hand
and tear/abrasion resistance to said textile, said resin-reactive modifier
comprising reactive groups capable of forming a covalent bond with said
durable-press resin, and optionally, iii) a catalyst;
removing said treated textile from the aqueous solution;
drying said treated textile; and
curing said treated textile;
said treated textile having the characteristic of exhibiting durable wrinkle resistance, soft
hand, and tear/abrasion resistance.

12. A treated textile according to Claim 11 wherein said resin-reactive modifier comprises reactive building blocks and rubbery building blocks.

5 13. A treated textile according to Claim 12 wherein said resin-reactive modifier comprises at least one hydroxyl reactive group per molecule.

14. A treated textile according to Claim 12 wherein said resin-reactive modifier is selected from the group consisting of butadiene polymer and hydrogenated butadiene polymer comprising at least one hydroxyl reactive group per molecule.

10

15. A treated textile according to Claim 12 wherein said durable-press resin is DMDHEU.

16. A resin-reactive modifier which comprises reactive groups capable of forming a covalent bond with a durable-press resin and which is capable of imparting a soft hand and tear/abrasion resistance to a textile.

15

17. A resin-reactive modifier according to Claim 16 which comprises reactive building blocks and rubbery building blocks.

20

18. A resin-reactive modifier according to Claim 17 which comprises at least one hydroxyl reactive group per molecule.

25

19. A resin-reactive modifier according to Claim 17 which is selected from the group consisting of butadiene polymer and hydrogenated butadiene polymer comprising at least one hydroxyl reactive group per molecule.